

**METHOD FOR COMMON CONTROL OF THE BANDWIDTHS OF A GROUP OF
INDIVIDUAL INFORMATION FLOWS**

CLAIM FOR PRIORITY

5 This application claims priority to International Application
No. PCT/EP02/04113 which was published in the German language
on April 12, 2002.

TECHNICAL FIELD OF THE INVENTION

10 The invention relates to a method and device for transmitting
traffic streams over a common transmission channel.

BACKGROUND OF THE INVENTION

If a number of traffic streams (with payload data packets, for
example voice or multimedia data) are to be transmitted over a
15 common transmission channel (for example through a core net of
a mobile radio network) access control in the form of
distribution of the bandwidth of the common transmission
channel to the traffic streams to be transmitted on this
transmission channel is required. In such cases each of the
20 traffic streams can be assigned a "guaranteed bandwidth" which
is securely available to the traffic stream as a proportion of
the bandwidth of the transmission channel independently of
traffic load in the other traffic streams. Furthermore, what
is referred to as a maximum bandwidth can be defined, which is
25 greater than the guaranteed bandwidth and which specifies how
much bandwidth (volume of data to be transmitted per unit of
time etc.) is available to this traffic stream on the common
transmission channel. As a rule, the maximum bandwidth for a
traffic stream is significantly greater than the bandwidth

guaranteed for this traffic stream in the transmission channel.

To best utilize a common transmission channel for cost optimization purposes the greatest number of traffic streams possible (each with a guaranteed bandwidth) should as a rule be allowed for the common transmission channel, however at the same time the bandwidth guarantees of the individual traffic streams should not be violated, even if the transmission channel is overbooked and many traffic streams often attempt to utilize their maximum allowed bandwidth.

According to the 3 GPP Technical Specification 23.107 ([www.http:\\www.3GPP.org](http://www.3gpp.org)) there exist for traffic streams of the traffic classes defined there "conversational" etc. as so-called QoS (Quality of Service) parameters including the "maximum bandwidth" and "guaranteed bandwidth" variable. At what are known as CORE Network GATEWAYS (CNGW) the situation can occur that for downlinks the own control streams, that is streams from an external network as seen by the UMTS core network into the UMTS core network (further in the direction of mobile terminals) the maximum bandwidth must be monitored and these streams in the direction of the core network on one or more transmission channels, which are each shared by a number of downlink streams, must be ensured the guaranteed bandwidth.

Access procedures known to the expert for allocating transmission channel bandwidth capacities to traffic streams are based for example on statistical mean values which are assumed for each traffic stream (supplemented by a security margin for cases where by chance many traffic streams simultaneously exceed the estimated mean value) or a measurement of the current load in the traffic streams to be

transmitted over the transmission channel. A weighted fair queuing scheduler for the one queue per traffic stream for example ensures that each traffic stream can use at least one guaranteed bandwidth and a maximum of the maximum bandwidth
5 assigned to it for transmitting packets over the common transmission channel. The disadvantage of this process is that this scheduler is expensive to implement and exhibits efficiency problems with a large number of traffic streams, so that realistically it can only be used for 1,000 traffic
10 streams per transmission channel.

SUMMARY OF THE INVENTION

The present invention allows simple and efficient transmission which is also suitable for transmitting a large number of traffic streams over a common transmission channel, which for
15 each of the traffic streams, complies with the "guaranteed bandwidth" and still enables efficient utilization of the transmission capacity of the transmission channel. Since the invention defines (at least) three different priorities for onwards transmission over the transmission channel for
20 incoming packets of a traffic stream and the transmission of packets of a traffic stream arriving in the buffer over the transmission channel is prioritized depending on this relative to each other with the bandwidth with which the packets arrived in the buffer, it is possible to ensure that the
25 secured "guaranteed bandwidths" in the traffic streams are adhered to and a good utilization of the bandwidth of the transmission channel and a suitable prioritization of the packets of a traffic stream is made possible.

The method which can be implemented very simply and
30 efficiently by comparison to the weighted fair queuing scheduler method is also especially suitable for transmission

of more than 1,000 traffic channels over one transmission channel. A method in accordance with the invention can especially be used for traffic channels in the form of mobile radio channels for payload data (voice, alphanumeric data).

5 BRIEF DESCRIPTION OF THE DRAWINGS

Further features and advantages of the invention emanate from the subsequent description of an exemplary embodiment on the basis of the drawing. The Figures show

10 Figure 1 an example of transmission of data in a number of traffic streams over a common transmission channel and

Figure 2 a schematic diagram of the use of bandwidths in a transmission channel.

15 According to Figure 1 packets A-E of a first traffic stream 1 come into a first buffer 4, data packets F-J of a second traffic stream 2 come into a second buffer 5, data packets K-O of a third traffic stream 3 come into a buffer 6, where data packets A-O are all to be transmitted via a transmission channel 7 (common for traffic streams 1-3) (for example over
20 the core net of a mobile radio network etc.), in which case they are divided up again here after transmission over the common transmission channel 7 into a first traffic stream 8, a second traffic stream 9 and a third traffic stream 10 for separate further transmission.

25 The traffic stream data transferred in the packets A-E, F-J and K-U can for example be voice data of a mobile radio network or voice-related data (e-mails, Internet pages), where for example a traffic

stream can transmit one or more calls in one direction.

Instead of using a buffer for each traffic stream, as shown here, a common buffer can also be used for all incoming traffic streams 1-3 in one transmission channel 7. The packets
5 of the traffic streams should already be identified in the buffer in such a way that they can be split up again beyond the buffer into the individual traffic streams 8 - 10.

Before explaining the inventive sequence of the transmission of packets 4 - 6 in the common transmission channel 7, Figure
10 2 is used to show the subdivision of the available bandwidth of the transmission channel B_{g0} into guaranteed bandwidths B_{G1} , B_{G2} , B_{G3} for the individual traffic streams 1 - 3 in the common transmission channel 7.

Figure 2 shows schematically the entire bandwidth available in a transmission channel B_{g0} which is divided up into a number of
15 traffic streams 1 - 3. Here in the present case, traffic stream 1 is given a guaranteed bandwidth B_{G1} , traffic stream 2 a guaranteed bandwidth B_{G2} and the third traffic stream 3 a guaranteed bandwidth B_{G3} . The guaranteed bandwidth of a traffic
20 stream is available to it regardless of the actual bandwidth used by the other traffic streams (is also guaranteed). The bandwidth actually used by a transmission channel can be greater than the guaranteed bandwidth for the channel if the sum of the guaranteed bandwidths is less than the overall
25 bandwidth of the transmission channel or if the sum of the

guaranteed bandwidths plus the bandwidth used over and above
 this in a traffic stream is greater than the overall bandwidth
 of the transmission channel and with many traffic streams in a
 transmission channel there is little likelihood of a violation
 5 of the bandwidth guarantees occurring. In addition to the
 traffic streams 1 - 3 already booked into a transmission
 channel 7 a further traffic stream is only allowed if the sum
 of the guaranteed bandwidths for traffic streams plus the
 guaranteed bandwidth requested for the new traffic stream is
 10 less than the product of a quality factor constant with the
 entire bandwidth of the transmission channel. Whereas with a
 quality factor constant = 1 there is a full utilization of the
 transmission channel with guaranteed bandwidths (so that the
 maximum bandwidth of a traffic stream is no greater or only
 15 insignificantly greater than the guaranteed bandwidth of the
 traffic stream, with a quality factor constant < 1 with bursts
 congestion in the buffer is cleared relatively quickly,
 whereas with a quality factor constant > 1 there is an
 overbooking of the transmission channel with traffic streams,
 20 so that bandwidth guarantees may not be adhered to, but the
 transmission channel is statistically largely booked out.

According to the model explained on the basis of Figure 2 each
 traffic stream will be assigned a guaranteed bandwidth in the
 transmission channel which is securely available to it, as
 25 well as a maximum bandwidth in the transmission channel which
 as a rule is greater than the guaranteed bandwidth. The
 sequence in which packets arriving in a traffic stream 1 are
 transmitted over the transmission channel depends on the
 transmission rate with which packets of a

traffic stream arrive (in a buffer before the transmission channel).

This can take account of the timing gap between the packets (especially with packets of the same length) and/or how

5 extensive the packets are (especially with packets of different lengths). The packets arriving in the buffer are given a marking which takes account of this transmission rate (input bandwidth in the buffer) of these packets (for example in a header in the packet), on the basis of which the packet
10 is selected for transmission over the transmission channel 7, which defines the sequence of its transmission.

For example packets which arrive in the buffer 4 with a transmission rate below the bandwidth guaranteed by the transmission channel for the traffic stream are marked as
15 "green" (or as a rule given a number in the header of the packet), packets which arrive with a transmission rate lying between the guaranteed bandwidth and the maximum bandwidth of the traffic stream are marked "amber" (or as a rule given a number in the header of the packet) and packets which arrive
20 with a transmission rate greater than the maximum bandwidth of the traffic stream are marked "red" (or as a rule given a number in the header of the packet). A marking in packets of a traffic stream (1) thus defines the order in which the packets of this traffic stream (1) will be transmitted but not the
25 order in which packets of another traffic stream will be transmitted.

For example if the packets A, B (and possibly numerous packets arriving before these) arrive in buffer 4 for traffic stream 1 with a transmission rate which is above the guaranteed
30 bandwidth of the

traffic stream but below the maximum bandwidth of the traffic stream 1, they are marked "amber". Packet C arrives shortly after packet B with a transmission rate which is above the maximum bandwidth, so that this packet is marked "red".

- 5 Packets D and E arrive in the buffer with a transmission rate which is below the guaranteed bandwidth of the traffic stream 1 and are marked "green" in their header etc.

The same applies to traffic streams 2 and 3. In the case discussed here the guaranteed bandwidths for each transmission
10 channel are adhered to for the transmission of the packets of traffic streams 1 to 3 over the common transmission channel 7 and thus the maximum bandwidths per traffic channel are still adhered to as far as possible. If, as in the case discussed here, the guaranteed bandwidths and maximum bandwidths for the
15 three traffic streams 1 to 3 are the same size in each case, in the simplest cases one packet of each of traffic streams 2,3 can be transmitted in turn. In this case each packet D, E (green), of a traffic stream 1 which arrives in a buffer 4 with a guaranteed bandwidth below that for this traffic stream
20 1 for the transmission channel 7, is timed to be transmitted into the buffer 4 before all packets A, B, C, which are marked as arriving in buffer 4 with a transmission rate lying above the guaranteed bandwidth of this traffic stream (amber, red). In addition a packet of a traffic stream which is already in
25 the (at least one) buffer 4 and is marked as having arrived in buffer (4) with a transmission rate of between the guaranteed bandwidth and the maximum bandwidth of this traffic stream (for the transmission in the transmission channel 7), is timed to be transmitted from the

buffer into transmission channel 7 before all packets C arriving in the buffer 4 (red) with a transmission rate lying above the maximum transmission rate of traffic stream 1 (for transmission in transmission channel 7) (i.e. B, D before C).

- 5 In such cases all packets which have arrived with a comparable transmission rate in the buffer (all red or all amber or all green packets) are timed for transmission relative to one another in the order of their arrival.

This means that the packets of traffic stream 1 previously
10 arrived in the buffer and stored in buffer 4 in accordance with Figure 1 are transmitted in the following order: DEABC. The same applies to the packets of traffic streams 2, 3.

This means that, within the transmission channel 7, for
15 example every third packet (for the bandwidth distribution present here) is filled with packets of traffic stream 1 in the order specified for these packets (D, E, A, B, C). The intervening packets are filled in accordance with the packets of traffic stream 2 and of traffic stream 3.

Before transmission over transmission channel 7 packets of a
20 traffic stream 1 are each marked with an entry defining this traffic stream 1 (e.g. "1" in the header of the packet) and after the transmission channel are sorted again if necessary into a traffic stream, so that after the transmission channel 7 the traffic streams can again be forwarded individually.

25 Further it can be prespecified in the example shown here for data packets of different priority (priority-red packet, priority-amber packet priority-green packet) after how much time they are discarded

in the buffer. It makes sense for packets of priority "red" to expire before packets of priority "amber" and packets of priority "amber" before packets of priority "green".

5 This method provides a simple and efficient way, even with a large number of traffic streams in a transmission channel, of adhering to bandwidth guarantees and also makes a high maximum transmission rate possible.